



MATERIAL SAFETY DATA SHEET

PROVEN BRAND GLOSS WHITE LACQUER 05016

1. Product And Company Identification	
Supplier Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA Company Contact: Aludia B. Hernandez Telephone Number: 708-865-1000 FAX Number: 708-865-0923 E-Mail: sales@chaseproducts.com Web Site: www.chaseproducts.com	Manufacturer Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA Company Contact: Aludia B. Hernandez Telephone Number: 708-865-1000 FAX Number: 708-865-0923 E-Mail: sales@chaseproducts.com Web Site: www.chaseproducts.com
Supplier Emergency Contacts & Phone Number Chem-Tel: 1-800-255-3924	Manufacturer Emergency Contacts & Phone Number Chem-Tel: 1-800-255-3924
Issue Date: 01/13/2004 Product Name: PROVEN BRAND GLOSS WHITE LACQUER 05016 Chemical Name: 6-5314-2 CAS Number: Not Established MSDS Number: 2296 Product Code: 429-6082 Product/Material Uses - Spray Paint	

2. Composition/Information On Ingredients			
Ingredient Name	CAS Number		Percent Of Total Weight
2-BUTOXYETHANOL	111-76-2	<=	1
ACETONE	67-64-1		
BUTANE	106-97-8		
BUTYL ACETATE	123-86-4		
DIACETONE ALCOHOL	123-42-2		
ISOBUTYL ALCOHOL	78-83-1		
ISOPROPYL ALCOHOL	67-63-0		
METHYL ETHYL KETONE	78-93-3		1 - 5
PROPANE	74-98-6		
TOLUENE	108-88-3		10 - 15
Hazardous components, according to OSHA, are listed when present at 1.0% or greater, carcinogenes are listed when present at 0.1% or greater.			

3. Hazards Identification
Primary Routes(s) Of Entry - Ingestion (possible, but considered unlikely), eye contact, skin contact, inhalation. Eye Hazards - Causes eye irritation. Skin Hazards - Causes skin irritation. Ingestion Hazards - This is an aerosol product, ingestion is unlikely to occur. Contains solvents, harmful if swallowed. If accidentally swallowed, do not induce vomiting. Call physician immediately. Inhalation Hazards - Deliberate inhalation of concentrate vapor or mist may cause headache, dizziness and nausea..

MATERIAL SAFETY DATA SHEET

PROVEN BRAND GLOSS WHITE LACQUER 05016

3. Hazards Identification - Continued

Chronic/Carcinogenicity Effects - Toluene and xylene have been associated with kidney and liver disorders. Contains less than 1% xylene and less than 0.1% ethylbenzene. IARC has evaluated and classified ethylbenzene as a possible human carcinogen (group 2B) based on sufficient evidence of carcinogenicity in animals, but inadequate evidence for cancer in exposed humans.

Epidemiology - None known

Teratogenicity (Birth Defects) - California's Proposition 65: "Warning: this product contains toluene, a chemical known to the State of California to cause birth defects or other reproductive harm".

Reproductive Effects - Suspect reproductive hazard. Contains material which may cause birth defects, based on animal data. This product contains toluene.

Neurotoxicity - None known


Mutagenicity (Genetic Effect) - None known

Signs And Symptoms - Acute: Prolonged inhalation of vapor or mist may cause headache, dizziness and nausea. Prolonged contact with the skin causes irritation. Irritant to eyes.

Conditions Aggravated By Exposure - Pre-existing skin, respiratory, liver and kidney disorders.

Conditions Aggravated By Overexposure - Pre-existing skin, respiratory, liver and kidney disorders.

First Aid (Pictograms)



4. First Aid Measures

Eye - Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

Skin - Wash skin with soap and water. If irritation develops, call a poison control center or doctor for treatment advice.

Ingestion - Ingestion from an aerosol product is unlikely to occur. Contains solvents. Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician immediately.

Inhalation - If overcome by vapor move victim to fresh air. Provide artificial respiration if necessary. Consult a physician if injury develops.

5. Fire Fighting Measures

Flash Point: Not available °F Not available °C

Flash Point Method: Not available

Lower Explosive Limit: Not available

Upper Explosive Limit: Not available

Fire And Explosion Hazards - This product is an aerosol product for which **Flame Projection is 18 in, with flashback.** Temperatures above 120 F may cause cans to burst.

Extinguishing Media - Use CO2 (Carbon Dioxide), dry chemical, or water fog.

Fire Fighting Instructions - Water spray may be used to cool cans in the vicinity of fire or excessive heat.

6. Accidental Release Measures

Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.

MATERIAL SAFETY DATA SHEET

PROVEN BRAND GLOSS WHITE LACQUER 05016

6. Accidental Release Measures - Continued

Handling & Storage (Pictograms)



7. Handling And Storage

Handling And Storage Precautions - Handle as an extremely flammable material. Store in a cool, dry place away from heat and open flame.

Handling Precautions - Avoid getting spray into eyes. Keep out of reach of children.

Storage Precautions - Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

AEROSOL STORAGE LEVEL III (NFPA-30B)

Work/Hygienic Practices - Wash hands thoroughly after using this product.

Protective Clothing (Pictograms)



8. Exposure Controls/Personal Protection

Engineering Controls - Use with adequate general and local exhaust ventilation.

Eye/Face Protection - Conventional eyeglasses to guard against splashing.

Skin Protection - Rubber, vinyl or household type gloves.

Respiratory Protection - Use in well-ventilated area ONLY. NOTICE: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or use an appropriate, properly fitted respirator (NIOSH approved), or leave the area. NOTE: Follow respirator manufacturer's instructions carefully.

Ingredient(s) - Exposure Limits

2-BUTOXYETHANOL

ACGIH TLV-TWA 20 ppm (Skin) ; OSHA PEL-TWA 50 ppm (Skin)

ACETONE

ACGIH TLV-STEL 750 ppm ; ACGIH TLV-TWA 500 ppm ; OSHA PEL-TWA 1,000 ppm

BUTANE

ACGIH TLV-TWA 800 ppm

BUTYL ACETATE

ACGIH TLV-STEL 200 ppm ; ACGIH TLV-TWA 150 ppm ; OSHA PEL-TWA 150 ppm

DIACETONE ALCOHOL

ACGIH TLV-TWA 50 ppm ; OSHA PEL-TWA 50 ppm

ISOBUTYL ALCOHOL

ACGIH TLV-TWA 50 ppm ; OSHA PEL-TWA 100 ppm

ISOPROPYL ALCOHOL

ACGIH TLV-STEL 500 ppm (Notice of Intended Change) ; ACGIH TLV-STEL 400 ppm (Proposed) ; ACGIH TLV-TWA 400 ppm (Notice of Intended Change)

ACGIH TLV-TWA 200 ppm (Proposed) ; OSHA PEL-TWA 400 ppm

METHYL ETHYL KETONE

ACGIH TLV-STEL 300 ppm ; ACGIH TLV-TWA 200 ppm ; OSHA PEL-TWA 200 ppm

PROPANE

MATERIAL SAFETY DATA SHEET

PROVEN BRAND GLOSS WHITE LACQUER 05016

8. Exposure Controls/Personal Protection - Continued

Ingredient(s) - Exposure Limits - Continued

ACGIH TLV-TWA 2500 ppm ; OSHA PEL-TWA 1,000 ppm

TOLUENE

ACGIH TLV-TWA 50 ppm (Skin) ; OSHA PEL-CEILING 300 ppm ; OSHA PEL-PEAK 500 ppm

OSHA PEL-TWA 200 ppm

9. Physical And Chemical Properties

Appearance - Appearance of paint.

Odor - Paint odor.

Chemical Type: Mixture

Physical State: Liquid

Melting Point: Not applicable °F Not applicable °C

Boiling Point: Acetone 113 °F Acetone 56 °C

Specific Gravity: 0.938

Percent VOCs: 51.27

Solubility: Insoluble

Evaporation Rate: Faster than butyl acetate

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Conditions To Avoid (Stability) - Temperatures above 120 F

Incompatible Materials - Avoid heat, open flame and contact with strong oxidizers.

Hazardous Decomposition Products - Thermal decomposition may yield gases like carbon monoxide and carbon dioxide.

Conditions To Avoid (Polymerization) - Temperatures above 120 F

11. Toxicological Information

No Data Available...

12. Ecological Information

No Data Available...

13. Disposal Considerations

Do not puncture or incinerate container. **If empty:** Place in garbage or offer for recycling if available. **If partly filled:** Call your local solid waste agency for disposal instructions.

14. Transport Information

Proper Shipping Name - ORM-D Consumer Commodity

Hazard Class

2.1

DOT Identification Number

UN1950

DOT Shipping Label

Aerosol Consumer Commodity

MATERIAL SAFETY DATA SHEET

PROVEN BRAND GLOSS WHITE LACQUER 05016

15. Regulatory Information

U.S. Regulatory Information - All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SARA Hazard Classes

Acute Health Hazard; Chronic Health Hazard; Fire Hazard

SARA Section 313 Notification - This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material. 2-Butoxyethanol, Methyl ethyl ketone, Toluene See section 2 for % amounts in the product.

Ingredient(s) - U.S. Regulatory Information

2-BUTOXYETHANOL

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical; SARA - Acute Health Hazard; SARA - Chronic Health Hazard; SARA - Fire Hazard

METHYL ETHYL KETONE

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical; SARA - Acute Health Hazard; SARA - Chronic Health Hazard; SARA - Fire Hazard

TOLUENE

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical; SARA - Acute Health Hazard; SARA - Chronic Health Hazard; SARA - Fire Hazard

Ingredient(s) - State Regulations

2-BUTOXYETHANOL

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

ACETONE

New Jersey - Workplace Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

BUTANE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

BUTYL ACETATE

New Jersey - Workplace Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Pennsylvania - Environmental Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

DIACETONE ALCOHOL

New Jersey - Workplace Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

ISOBUTYL ALCOHOL

New Jersey - Workplace Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Pennsylvania - Environmental Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

ISOPROPYL ALCOHOL

New Jersey - Workplace Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

METHYL ETHYL KETONE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania -

MATERIAL SAFETY DATA SHEET

PROVEN BRAND GLOSS WHITE LACQUER 05016

15. Regulatory Information - Continued

Ingredient(s) - State Regulations - Continued

Workplace Hazard; Pennsylvania - Environmental Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

PROPANE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

TOLUENE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Pennsylvania - Environmental Hazard; California - Proposition 65; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

NFPA



HMIS

HEALTH	*2
FLAMMABILITY	4
REACTIVITY	1
PERSONAL PROTECTION	B

16. Other Information

Revision/Preparer Information

MSDS Preparer: Laura E. Radevski

MSDS Preparer Phone Number: 708-865-1000

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

Chase Products Co.

Printed Using MSDS Generator™ 2000